



UL LLC
1075 W Lambert Rd Suite B
Brea, CA 92821

Integrating Sphere Test Report

Relevant Standards
IES LM-79-2008, ANSI C82.77-2002, CIE 13.3-1995
CIE 15-2004, ANSI C78.377-2015, IES TM-30-2015

Prepared For
B-K Lighting Inc
Chris McCarthy
40429 Brickyard Dr
Madera, CA 93636-9515
United States

Catalog Number
LTL-X44-LED
Order Number
12033910
Test Number
12033910.04

Test Date

2017-11-08

Prepared By

William Escobar, Technician

Approved By

Eric Gaudreau, Senior Engineering Associate

The results contained in this report pertain only to the tested sample.
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.
This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.



Luminaire Description: Decorative white metal housing with louvers and frosted lens
Lamp: One (1) white LED with optic
Mounting: Post
Ballast/Driver: One (1) ECOdrive 561/S

Luminaire



Summary of Results

Radiant Flux:	6578 mW
Luminous Flux:	2132 lm
Luminaire Efficacy:	62.8 lm/W
CCT:	3116 K
CRI (Ra):	83.0
Chromaticity (x):	0.4267
Chromaticity (y):	0.3967
Chromaticity (u):	0.2471
Chromaticity (v):	0.3446
Duv:	-0.0019

Test Conditions

Test Temperature:	25.0 °C
Voltage:	120.0 VAC
Current:	0.2848 A
Power:	33.96 W
Power Factor:	0.994
Frequency:	60 Hz
Current THD:	6.11 %

Testing was performed in a 2-meter integrating sphere using the 4 π geometry method.
Absorption correction was employed for this measurement.





Color Quality - Integrating Sphere

Integrating Sphere Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
25.0 °C	120.0 VAC	0.2848 A	33.96 W	0.994	60 Hz	6.11 %

Summary of Results

Total Output:	2132 Lumens	Chromaticity (x):	0.4267
Efficacy:	62.8 lm/w	Chromaticity (y):	0.3967
CCT:	3116 K	Chromaticity (u'):	0.2471
CRI (Ra):	83.0	Chromaticity (v'):	0.5169
CRI (R9):	9.7	TM-30 Rf:	83
Peak Wavelength:	603.3 nm	TM-30 Rg:	97
Dominant Wavelength:	582.9 nm	Duv:	-0.0019
S/P Ratio:	1.398		



Color Rendering Index Detail

Ra (CRI)	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.0	81.5	91.2	96.2	81.0	81.9	89.0	83.0	60.4	9.7	79.8	80.3	72.7	83.9	98.5	74.9

